


**Fiber optic diffuse reflection sensor**

FT-00-MPV-M6

**Application**

Function principle	Diffuse reflection sensor
Application	Robust design for use in harsh industrial environments; Resistant to various aggressive chemicals

**Monitoring range**

Range with fiber optic amplifier type	OKF; OUF; OOF
---------------------------------------	---------------

OKF

Range fiber optics [mm]	20
-------------------------	----

OOF

Range fiber optics [mm]	220
-------------------------	-----

OUF

Range fiber optics [mm]	20
-------------------------	----

**Operating conditions**

Ambient temperature [°C]	-20...80
--------------------------	----------

# E20511



## Fiber optic diffuse reflection sensor

FT-00-MPV-M6

Mechanical data		
Weight	[g]	58.5
Version of sensing head		straight
Sensing head thread		M6
Sensing head diameter	[mm]	7
Sensing head length	[mm]	45
Total length	[mm]	600
Min. bending radius	[mm]	20
Fiber arrangement		◎
Fiber material		PMMA
Fiber head material		stainless steel (1.4305 / 303)
Fiber sheath material		metal silicone
Accessories		
Items supplied		Hexagon nuts: 2 x M6, stainless steel tooth lock washers: 2 Knurled nut: 1 x M11
Remarks		
Pack quantity		1 pcs.