


IF5313

IF-3002-BPKG/55V

Inductive sensors



Product characteristics

Inductive sensor
Plastic thread M12 x 1
Cable
Sensing range 2 mm; [f] flush mountable

Electrical data

Electrical design	DC PNP
Operating voltage [V]	10...55 DC
Current consumption [mA]	15 (24 V)
Protection class	II
Reverse polarity protection	yes

Outputs

Output function	normally open
Voltage drop [V]	< 2.5
Current rating [mA]	250
Short-circuit protection	pulsed
Overload protection	yes
Switching frequency [Hz]	800

Range

Sensing range [mm]	2
Real sensing range (Sr) [mm]	2 ± 10 %
Operating distance [mm]	0...1.6

Accuracy / deviations

Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / Al approx. 0.3 / Cu approx. 0.2
Hysteresis [% of Sr]	1...15
Switch-point drift [% of Sr]	-10...10

Environment

Ambient temperature [°C]	-25...80
Protection	IP 67

Tests / approvals

EMC	EN 60947-5-2 EN 55011: class B
MTTF [Years]	945

Mechanical data

Mounting	flush mountable
Housing materials	PBT
Weight [kg]	0.091

IF5313

IF-3002-BPKG/55V

Inductive sensors

Displays / operating elements

Output status indication LED yellow

Electrical connection

Connection PVC cable / 2 m; 3 x 0.34 mm²


Wiring

Core colours

BN brown

BU blue

BK black



Accessories

Accessories (included) 2 lock nuts

Remarks

Pack quantity [piece] 1