


MGS204

MGK3070-BPKG/AM/G/US

Magnetic sensors, cylinder sensors



Product characteristics

Magnetic sensor with GMR cell
Metal thread M18 x 1
Quick disconnect
Full metal housing
gold-plated contacts
Sensing range 70 mm; referred to magnet M4.0
Magnetic sensitivity 0.9 mT

Electrical data

Electrical design	DC PNP
Operating voltage [V]	10...30 DC
Current consumption [mA]	< 10
Protection class	III
Reverse polarity protection	yes

Outputs

Output function	normally open
Voltage drop [V]	< 2.5
Current rating [mA]	200
Short-circuit protection	yes
Overload protection	yes
Switching frequency [Hz]	5000

Monitoring range

Sensing range [mm]	70, referred to magnet M4.0
Magnetic sensitivity [mT]	0.9

Accuracy / deviations

Hysteresis [% of Sr]	1...10
----------------------	--------

Environment

Ambient temperature [°C]	-25...75
Protection	IP 65 / IP 67

Tests / approvals

EMC	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 10 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-5 Surge: 0.5 kV (line to line, Ri: 20hm) EN 61000-4-6 HF conducted: 10 V EN 55011 (Emission): class B DIN ISO 7637-2: 100 V/m
MTTF [Years]	1370

MGS204

MGK3070-BPKG/AM/G/US

Magnetic sensors, cylinder sensors

Mechanical data

Housing materials	housing: stainless steel (316L); active face: stainless steel (316L); connector: PA (polyamide); lock nuts: brass
Weight [kg]	0.05


Displays / operating elements

Output status indication	LED	yellow
--------------------------	-----	--------

Electrical connection

Connection	M12 connector; gold-plated contacts
------------	-------------------------------------

Wiring



Accessories

Accessories (included)	2 lock nuts
------------------------	-------------

Remarks

Pack quantity	[piece]	1
---------------	---------	---