


NF5030

IFA2004-N/V2A/6M/1D/1G

Inductive sensors



Product characteristics

Inductive sensor
Metal thread M12 x 1
Cable
ATEX approval
Group II, category 1D
Group II, category 1G/2G
Sensing range 4 mm; [nf] non-flush mountable

Electrical data

Electrical design	Connection to certified intrinsically safe circuits with the max. values U = 15 V / I = 50 mA / P = 120 mW
Nominal voltage [V]	8.2 DC; (1kΩ)
Supply voltage [V]	7.5...30 DC; when used outside the hazardous area
Current consumption [mA]	< 1 disabled; (> 2.1 mA enabled)
Protection class	III

Outputs

Output function	normally closed
Current rating [mA]	< 30; when used outside the hazardous area
Switching frequency [Hz]	1500

Monitoring range

Sensing range [mm]	4
Real sensing range (Sr) [mm]	4 ± 10 %

Accuracy / deviations

Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3
Hysteresis [% of Sr]	1...15
Switch-point drift [% of Sr]	-10...10

Environment

Ambient temperature [°C]	-20...80
Protection	IP 67

Tests / approvals

Approval	PTB 01 ATEX 2191 BVS 04 ATEX E153 TIIS TC16107
Marking of the unit	<p>⊕ II 1G Ex ia IIC T6 Ga Ta: -20...70° C</p> <p>⊕ II 1G Ex ia IIC T5 Ga Ta: -20...80° C</p> <p>⊕ II 1D Ex ia IIIC T90° C Da Ta: -20...70° C</p> <p>⊕ II 1D Ex ia IIIC T100° C Da Ta: -20...80° C</p>
EMC	EN 60947-5-6
Shock / vibration resistance	30 g (11 ms) / 10-55 Hz (1 mm)

NF5030

IFA2004-N/V2A/6M/1D/1G

Inductive sensors

MTTF	[Years]	5096
------	---------	------

Safety classification

Internal capacitance	[nF]	< 141
Internal inductance	[μH]	< 134

Mechanical data

Mounting		non-flush mountable
Housing materials		stainless steel; PBT
Weight	[kg]	0.253

Electrical connection


Connection		PVC cable / 6 m; 2 x 0.34 mm ²
------------	--	---

Wiring

Core colors

BN brown

BU blue



Accessories

Accessories (included)		2 lock nuts
------------------------	--	-------------

Remarks

Pack quantity	[piece]	1
---------------	---------	---