


# SF5350

SFD10ADB /6M

Flow sensors



1: internal thread M18 x 1.5



## Product characteristics

Flow sensor for connection to evaluation units

for adapter

Cable

Process connection: internal thread M18 x 1.5 for adapter

## Application

Application	liquids and gases
Pressure rating [bar]	300
Medium temperature [°C]	-25...80

## Electrical data

Connection to control monitor	VS3000
-------------------------------	--------

## Measuring / setting range

Liquids	
Setting range [cm/s]	3...300
Greatest sensitivity [cm/s]	3...60
Gases	
Setting range [cm/s]	200...3000
Greatest sensitivity [cm/s]	200...800

## Accuracy / deviations

Max. temperature gradient of medium [K/min]	300
---	-----

## Reaction times

Response time [s]	1...10
-------------------	--------

## Environment

Protection	IP 67
------------	-------

## Tests / approvals

Shock resistance	DIN IEC 68-2-27:	40 g (11 ms)
Vibration resistance	DIN IEC 68-2-6:	10 g (55...2000 Hz)
MTTF [Years]		8213

## Mechanical data

Process connection	internal thread M18 x 1.5 for adapter
Materials (wetted parts)	stainless steel 316L / 1.4404; O-ring: FKM 8 x 1.5 gr 80° Shore A
Housing materials	stainless steel 316L / 1.4404
Probe length L [mm]	45
Weight [kg]	0.401

## Electrical connection

**SF5350**

SFD10ADB /6M


**Flow sensors**

Connection	PUR cable / 6 m; 5 x 0.34 mm <sup>2</sup>
Max. cable length [m]	100 (5 x 0.5mm <sup>2</sup> )

**Wiring**

Core colors

BN brown  
 BU blue  
 BK black  
 WH white  
 GY grey


**Remarks**

Pack quantity [piece]	1
-----------------------	---