


**VSE100**

DIAGNOSTIC ELECTRONICS

Diagnostic systems



1: Ethernet interface

**Product characteristics**

Diagnostic electronics for vibration sensors

VSE

Plastic housing

Combicon connection

Integrated history memory with real-time clock

Counter function

TCP/IP Ethernet interface

Active wire break detection and self-test (only MEMS) of the connected acceleration sensors

Parameter setting via PC software VES004

Electrical data

Operating voltage [V] 24 DC ± 20 % *)

Current consumption [mA] 200 (24 V)

Protection class III

Inputs / outputs

Circuit 4 inputs dynamic, can be configured individually: 0...10 mA, IPE or 0/4...20 mA
 2 inputs static: 0/4...20 mA (0...10 V) or pulse (electrically isolated)
 2 digital alarm outputs (PNP 100 mA) or 1 digital output and 1 analogue output 0/4...20/22 mA (0...10 V)

Inputs / outputs total 16, configurable

Dynamic (number) 4

Inputs

Dynamic input 0...10 mA, IPE or 0/4...20 mA

digital

Circuit HTL-Pegel

analog

Input pulses 0/4...20 mA or 0...10 V or pulse

Resolution [Bit] 12

Outputs

digital

Output OU 1 = switching output or analogue output / OU 2 (I/O 1...8) = switching output
 Output function normally open / closed programmable

**VSE100**

DIAGNOSTIC ELECTRONICS

Diagnostic systems

Max. current load per output	[mA]	100
Voltage drop	[V]	< 2
Short-circuit protection		yes (non-latching)
Overload protection		yes
analog		
current output	[mA]	0/4...20/22; or 0...10 V
Max. load	[Ω]	500
Measuring / setting range		
Sampling rate	[kSamples]	≤ 100
Software / programming		
History memory		Ring memory, FIFO (max. 881664 values)
Interfaces		
Data interface		Ethernet TCP/IP
Environment		
Ambient temperature	[°C]	0...70
Storage temperature	[°C]	0...70
Protection		IP 20
Tests / approvals		
EMC		EN 61000-6-2 EN 61000-6-3 EN 50178
MTTF	[Years]	89
Mechanical data		
Max. length of the sensor cable	[m]	250
Housing materials		PA
Type of mounting		Mounting on DIN rail
Weight	[kg]	0.357
Electrical connection		
Connection		Combicon
Wiring		


VSE100

DIAGNOSTIC ELECTRONICS

Diagnostic systems

- 1: L+ when a VSP acceleration sensor or an IEPE sensor 24 V DC ± 20% is used

- 9...24: Sensor-specific see operating instructions

**Accessories**

Accessories (optional)

crosslink cable for the direct connection of the diagnostic electronics VSExxx to the PC Ethernet interface

Remarks

Remarks

*) 24 V + 20% if an IEPE input is used (Integrated Electronics Piezo Electric)

Pack quantity

[piece]

1